



SAFETY DATA SHEET T-CUT ORIGINAL

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	T-CUT ORIGINAL
Product number	TCO002, TCO005, TCT304, TCT375, TCT501, TCT504, TCT506, TCT000, TMT500, TMT306

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Car maintenance product.
-----------------	--------------------------

1.3. Details of the supplier of the safety data sheet

Supplier	TETROSYL LIMITED Bury Lancashire England BL9 7NY 0161 764 5981 0161 797 5899 info@tetrosyl.com
Manufacturer	TETROSYL LIMITED Bury Lancashire England BL9 7NY 0161 764 5981 0161 797 5899 info@tetrosyl.com

1.4. Emergency telephone number

Emergency telephone	+44 (0)161 764 5981
---------------------	---------------------

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards	Flam. Liq. 3 - H226
Health hazards	Skin Irrit. 2 - H315 Eye Irrit. 2 - H319
Environmental hazards	Aquatic Chronic 3 - H412

Environmental	The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.
---------------	--

2.2. Label elements

T-CUT ORIGINAL

Pictogram



Signal word

Warning

Hazard statements

H226 Flammable liquid and vapour.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P233 Keep container tightly closed.
 P264 Wash contaminated skin thoroughly after handling.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P321 Specific treatment (see medical advice on this label).
 P332+P313 If skin irritation occurs: Get medical advice/ attention.
 P337+P313 If eye irritation persists: Get medical advice/ attention.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P501 Dispose of contents/ container in accordance with national regulations.

Supplementary precautionary statements

P240 Ground/ bond container and receiving equipment.
 P241 Use explosion-proof electrical equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

PETROLEUM DISTILLATES		30-<60%
CAS number: 64742-81-0	EC number: 265-184-9	REACH registration number: 01-2119462828-25-XXXX
Classification Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411		

T-CUT ORIGINAL

HYDROCARBONS, C9 - C11, n-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS 10-<30%		
CAS number: —	EC number: 919-857-5	REACH registration number: 01-2119463258-33-XXXX
Classification Flam. Liq. 3 - H226 STOT SE 3 - H336 Asp. Tox. 1 - H304		
2-2'-(OCTADEC-9-ENYLIMINO)BISETHANOL 1-<2.5%		
CAS number: 25307-17-9	EC number: 246-807-3	REACH registration number: 01-2119510876-35-0000
M factor (Acute) = 10	M factor (Chronic) = 1	
Classification Acute Tox. 4 - H302 Skin Corr. 1A - H314 Eye Dam. 1 - H318 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410		
AMMONIA ...100% 0.1-<0.3%		
CAS number: 1336-21-6	EC number: 215-647-6	
M factor (Acute) = 1		
Classification Skin Corr. 1B - H314 Eye Dam. 1 - H318 STOT SE 3 - H335 Aquatic Acute 1 - H400		

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Get medical attention if any discomfort continues. Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
Inhalation	If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Move affected person to fresh air at once. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Give plenty of water to drink. Get medical attention if a large quantity has been ingested. Show this Safety Data Sheet to the medical personnel.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Do not rub eye. Get medical attention if any discomfort continues.

T-CUT ORIGINAL

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure. Effects may be delayed. Keep affected person under observation.
Inhalation	May cause an asthma-like shortness of breath. Vapours may cause drowsiness and dizziness.
Ingestion	May cause discomfort if swallowed. May cause stomach pain or vomiting. May cause nausea, headache, dizziness and intoxication.
Skin contact	Prolonged or repeated contact with skin may cause irritation, redness and dermatitis.
Eye contact	May cause temporary eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations. If in doubt, get medical attention promptly.
-----------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Use fire-extinguishing media suitable for the surrounding fire. Extinguish with foam, carbon dioxide, dry powder or water fog.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	No unusual fire or explosion hazards noted.
Hazardous combustion products	Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting	No specific firefighting precautions known.
Special protective equipment for firefighters	Leave danger zone immediately.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Avoid inhalation of vapours. Provide adequate ventilation. In case of spills, beware of slippery floors and surfaces. For personal protection, see Section 8.
-----------------------------	---

6.2. Environmental precautions

Environmental precautions	Avoid or minimise the creation of any environmental contamination. Do not discharge into drains or watercourses or onto the ground. Collect and dispose of spillage as indicated in Section 13.
----------------------------------	---

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Stop leak if possible without risk. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Provide adequate ventilation. Contain spillage with sand, earth or other suitable non-combustible material. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely.
--------------------------------	--

6.4. Reference to other sections

T-CUT ORIGINAL

Reference to other sections For personal protection, see Section 8. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using the product. Avoid the formation of mists. Provide adequate ventilation. Read and follow manufacturer's recommendations. Do not handle broken packages without protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep containers upright. Store in tightly-closed, original container.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

No exposure limits known for ingredient(s).

PETROLEUM DISTILLATES

Long-term exposure limit (8-hour TWA): WEL 800 mg/m³

AMMONIA ...100%

Long-term exposure limit (8-hour TWA): WEL 18 mg/m³

Short-term exposure limit (15-minute): WEL 25 mg/m³

WEL = Workplace Exposure Limit

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients. This product must not be handled in a confined space without adequate ventilation.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Nitrile rubber. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended.

Other skin and body protection

Wear appropriate clothing to prevent repeated or prolonged skin contact. Provide eyewash station.

Hygiene measures

Wash contaminated clothing before reuse. Wash promptly with soap and water if skin becomes contaminated. Wash hands after contact. When using do not eat, drink or smoke.

T-CUT ORIGINAL

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Beige.
Odour	Slight. Ammonia.
Odour threshold	Scientifically unjustified. Scientifically unjustified.
pH	Scientifically unjustified.
Melting point	Scientifically unjustified.
Initial boiling point and range	>100°C @
Flash point	41°C
Evaporation rate	Scientifically unjustified.
Upper/lower flammability or explosive limits	Scientifically unjustified.
Vapour pressure	Scientifically unjustified.
Vapour density	Scientifically unjustified.
Relative density	1.050 - 1.070 g/cm ³ @ 20°C
Solubility(ies)	Forms an emulsion with water.
Partition coefficient	Scientifically unjustified.
Auto-ignition temperature	Scientifically unjustified.
Decomposition Temperature	Scientifically unjustified.
Viscosity	1510 @ 40°C
Oxidising properties	Not determined.

9.2. Other information

Other information None.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Not applicable.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

T-CUT ORIGINAL

Materials to avoid No specific material or group of materials is likely to react with the product to produce a hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition products Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 35,714.29

Inhalation Vapours may cause headache, fatigue, dizziness and nausea.

Ingestion May cause discomfort if swallowed.

Skin contact Product has a defatting effect on skin.

Eye contact Visual disturbances, including blurred vision.

Acute and chronic health hazards Inhalation May cause respiratory system irritation. SKIN CONTACT. Product has a defatting effect on skin. May cause allergic contact eczema. EYE CONTACT. Irritating to eyes. INGESTION. May cause stomach pain or vomiting.

SECTION 12: Ecological Information

Ecotoxicity The product contains substances which are toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

12.1. Toxicity

Acute toxicity - fish

LC₅₀, 96 hours: <30 mg/l (PETROLEUM DISTILLATES) mg/l, Algae

Acute toxicity - aquatic invertebrates

EC₅₀, 48 hours: 10 - 22 mg/l (PETROLEUM DISTILLATES) mg/l, Daphnia magna

Acute toxicity - aquatic plants

IC₅₀, 72 hours: 4.6 - 10.0 mg/l (PETROLEUM DISTILLATES) mg/l, Fish

12.2. Persistence and degradability

Persistence and degradability No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Scientifically unjustified.

12.4. Mobility in soil

Mobility The product is miscible with water and may spread in water systems.

Adsorption/desorption coefficient Not available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

T-CUT ORIGINAL

Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste is classified as hazardous waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods Confirm disposal procedures with environmental engineer and local regulations.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1993

UN No. (IMDG) 1993

UN No. (ICAO) 1993

14.2. UN proper shipping name

Proper shipping name (ADR/RID) FLAMMABLE LIQUID, N.O.S. (PETROLEUM DISTILLATES, PETROLEUM DISTILLATES)

Proper shipping name (IMDG) FLAMMABLE LIQUID, N.O.S. (PETROLEUM DISTILLATES, PETROLEUM DISTILLATES)

Proper shipping name (ICAO) FLAMMABLE LIQUID, N.O.S. (PETROLEUM DISTILLATES, PETROLEUM DISTILLATES)

Proper shipping name (ADN) FLAMMABLE LIQUID, N.O.S. (PETROLEUM DISTILLATES, PETROLEUM DISTILLATES)

14.3. Transport hazard class(es)

ADR/RID class 3

ADR/RID label 3

IMDG class 3

ICAO class/division 3

Transport labels



14.4. Packing group

ADR/RID packing group III

IMDG packing group III

ICAO packing group III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

EmS F-E, S-E

Emergency Action Code 3Y

T-CUT ORIGINAL

Hazard Identification Number 30
(ADR/RID)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations EH40/2005 Workplace exposure limits.

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision date 05/01/2017

Revision 31

Supersedes date 23/11/2016

SDS status Approved.

Hazard statements in full

H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.