



SAFETY DATA SHEET TRADE SPRAY GLOSS BLACK

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name TRADE SPRAY GLOSS BLACK

Product number ATS015

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Paint.

1.3. Details of the supplier of the safety data sheet

Supplier TETROSYL LIMITED
Bury
Lancashire
England
BL9 7NY
0161 764 5981
0161 797 5899
info@tetrosyl.com

Manufacturer TETROSYL LIMITED
Bury
Lancashire
England
BL9 7NY
0161 764 5981
0161 797 5899
info@tetrosyl.com

1.4. Emergency telephone number

Emergency telephone +44 (0)161 764 5981

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Aerosol 1 - H222, H229

Health hazards Eye Dam. 1 - H318 STOT SE 3 - H336

Environmental hazards Not Classified

2.2. Label elements

Pictogram



Signal word

Danger

TRADE SPRAY GLOSS BLACK

Hazard statements	<p>H222 Extremely flammable aerosol.</p> <p>H229 Pressurised container: may burst if heated</p> <p>H318 Causes serious eye damage.</p> <p>H336 May cause drowsiness or dizziness.</p>
Precautionary statements	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P211 Do not spray on an open flame or other ignition source.</p> <p>P251 Do not pierce or burn, even after use.</p> <p>P261 Avoid breathing vapour/ spray.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P310 Immediately call a POISON CENTER/ doctor.</p> <p>P312 Call a POISON CENTER/ doctor if you feel unwell.</p> <p>P403+P233 Store in a well-ventilated place. Keep container tightly closed.</p> <p>P405 Store locked up.</p> <p>P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p> <p>P101 If medical advice is needed, have product container or label at hand.</p> <p>P102 Keep out of reach of children.</p>
Contains	BUTYL ACETATE -norm, ACETONE, IPA, 1-METHOXY-2-PROPANOL, ISO-BUTANOL

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

ACETONE			30-<60%
CAS number: 67-64-1	EC number: 200-662-2		
Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336			
BUTYL ACETATE -norm			10-<30%
CAS number: 123-86-4	EC number: 204-658-1	REACH registration number: 01-2119485493-29-0000	
Classification Flam. Liq. 3 - H226 STOT SE 3 - H336			
PETROLEUM GASES, LIQUEFIED			5-<10%
CAS number: 68476-85-7	EC number: 270-704-2		
Classification Flam. Gas 1 - H220			

TRADE SPRAY GLOSS BLACK

XYLENE			2.5-<5.0%
CAS number: 1330-20-7	EC number: 215-535-7		
Classification Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315			

ISO-BUTANOL			2.5-<5.0%
CAS number: 78-83-1	EC number: 201-148-0	REACH registration number: 01-2119484609-23-0000	
Classification Flam. Liq. 3 - H226 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 STOT SE 3 - H335, H336			

2-METHOXY-1-METHYLETHYL ACETATE			2.5-<5.0%
CAS number: 108-65-6	EC number: 203-603-9	REACH registration number: 01-2119475791-29-0000	
Classification Flam. Liq. 3 - H226			

IPA			1-<2.5%
CAS number: 67-63-0	EC number: 200-661-7	REACH registration number: 01-2119457558-25-0000	
Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336			

1-METHOXY-2-PROPANOL			1-<2.5%
CAS number: 107-98-2	EC number: 203-539-1	REACH registration number: 01-2119457435-35-XXXX	
Classification Flam. Liq. 3 - H226 STOT SE 3 - H336			

TRADE SPRAY GLOSS BLACK

AMORPHOUS CARBON		0.5-<1%
CAS number: 1333-86-4	EC number: 215-609-9	REACH registration number: 01-2119384822-32-XXXX
Classification Not Classified		

ETHYLBENZENE		0.3-<0.5%
CAS number: 100-41-4	EC number: 202-849-4	
Classification Flam. Liq. 2 - H225 Acute Tox. 4 - H332 STOT RE 1 - H372 Asp. Tox. 1 - H304		

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Get medical attention if any discomfort continues. Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Effects may be delayed. Keep affected person under observation.
Inhalation	Remove affected person from source of contamination. If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Keep affected person under observation. Get medical attention. Show this Safety Data Sheet to the medical personnel. Symptoms of lung oedema (shortness of breath) may develop up to 24 hours after exposure. Get medical attention immediately.
Ingestion	Rinse mouth thoroughly with water. Give plenty of water to drink. Keep affected person under observation. Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs.
Skin contact	Wash skin thoroughly with soap and water. Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if any discomfort continues.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Do not rub eye. Get medical attention promptly if symptoms occur after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure. Effects may be delayed. Keep affected person under observation.
Inhalation	May cause an asthma-like shortness of breath. In case of overexposure, organic solvents may depress the central nervous system causing dizziness and intoxication, and at very high concentrations unconsciousness and death. Drowsiness, dizziness, disorientation, vertigo. Vapours may cause drowsiness and dizziness. Vapours in high concentrations are anaesthetic. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Central nervous system depression.

TRADE SPRAY GLOSS BLACK

Ingestion	May cause discomfort if swallowed. May cause stomach pain or vomiting. May cause nausea, headache, dizziness and intoxication. Due to the physical nature of this material it is unlikely that swallowing will occur.
Skin contact	Prolonged contact may cause redness, irritation and dry skin. May cause skin irritation/eczema.
Eye contact	Severe irritation, burning and tearing. Vapour, spray or dust may cause chronic eye irritation or eye damage. May cause blurred vision and serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations. If in doubt, get medical attention promptly.
-----------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with the following media: Foam, carbon dioxide or dry powder. Water spray. Use fire-extinguishing media suitable for the surrounding fire.
-------------------------------------	---

Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
---------------------------------------	--

5.2. Special hazards arising from the substance or mixture

Specific hazards	Containers can burst violently or explode when heated, due to excessive pressure build-up. Vapours may be ignited by a spark, a hot surface or an ember. Vapours may form explosive mixtures with air. Extremely flammable. Severe explosion hazard when vapours are exposed to flames. Risk of explosion if heated. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Containers can burst violently or explode when heated, due to excessive pressure build-up. Containers can burst violently or explode when heated, due to excessive pressure build-up.
-------------------------	--

Hazardous combustion products	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of carbon. Oxides of nitrogen.
--------------------------------------	--

5.3. Advice for firefighters

Protective actions during firefighting	Risk of re-ignition after fire has been extinguished. Risk of explosion. Cool containers exposed to flames with water until well after the fire is out. Use water to keep fire exposed containers cool and disperse vapours.
---	--

Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Wear protective clothing as described in Section 8 of this safety data sheet. Avoid inhalation of vapours. In case of spills, beware of slippery floors and surfaces.
-----------------------------	---

6.2. Environmental precautions

Environmental precautions	Avoid discharge into drains or watercourses or onto the ground. Collect and dispose of spillage as indicated in Section 13.
----------------------------------	---

6.3. Methods and material for containment and cleaning up

TRADE SPRAY GLOSS BLACK

Methods for cleaning up For waste disposal, see Section 13. If leakage cannot be stopped, evacuate area. Stop leak if possible without risk. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. Eliminate all sources of ignition. Wear suitable protective equipment for prolonged exposure and/or high concentrations of vapours, spray or mist. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using the product. Avoid inhalation of vapours/spray and contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Do not use in confined spaces without adequate ventilation and/or respirator. Mechanical ventilation or local exhaust ventilation may be required. Observe any occupational exposure limits for the product or ingredients. Avoid inhalation of vapours and spray/mists.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from heat, sparks and open flame. Keep containers upright. Protect against physical damage and/or friction. Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C. Do not store for long periods. Do not store in large quantities. Store in a cool and well-ventilated place. Keep container dry. Do not store near heat sources or expose to high temperatures.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

No exposure limits known for ingredient(s).

ACETONE

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³

BUTYL ACETATE -norm

Long-term exposure limit (8-hour TWA): WEL 150 ppm 724 mg/m³

Short-term exposure limit (15-minute): WEL 200 ppm 966 mg/m³

PETROLEUM GASES, LIQUEFIED

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m³

Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m³

Carc

XYLENE

TRADE SPRAY GLOSS BLACK

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m³

Sk

ISO-BUTANOL

Long-term exposure limit (8-hour TWA): WEL 50 ppm 154 mg/m³

Short-term exposure limit (15-minute): WEL 75 ppm 231 mg/m³

2-METHOXY-1-METHYLETHYL ACETATE

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 274 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 548 mg/m³(Sk)

IPA

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m³

Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m³

1-METHOXY-2-PROPANOL

Long-term exposure limit (8-hour TWA): WEL 100 ppm 375 mg/m³

Short-term exposure limit (15-minute): WEL 150 ppm 560 mg/m³

Sk

AMORPHOUS CARBON

Long-term exposure limit (8-hour TWA): WEL 3.5 mg/m³

Short-term exposure limit (15-minute): WEL 7 mg/m³

ETHYLBENZENE

Long-term exposure limit (8-hour TWA): WEL 100 ppm 441 mg/m³

Short-term exposure limit (15-minute): WEL 125 ppm 552 mg/m³

Sk

WEL = Workplace Exposure Limit

Carc = Capable of causing cancer and/or heritable genetic damage.

Sk = Can be absorbed through skin.

Sk = Can be absorbed through the skin.

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours and spray/mists. Observe any occupational exposure limits for the product or ingredients. Use explosion-proof general and local exhaust ventilation.

Eye/face protection

The following protection should be worn: Chemical splash goggles.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible.

Other skin and body protection

Provide eyewash station. Wear appropriate clothing to prevent repeated or prolonged skin contact.

Hygiene measures

Wash contaminated clothing before reuse. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap and water if skin becomes contaminated. Do not smoke in work area. When using do not eat, drink or smoke.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn.

SECTION 9: Physical and Chemical Properties

TRADE SPRAY GLOSS BLACK

9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Black.
Odour	Organic solvents.
Melting point	Not determined.
Initial boiling point and range	Technically not feasible.
Flash point	Technically not feasible.
Evaporation rate	Not determined.
Upper/lower flammability or explosive limits	Not determined.
Vapour pressure	Not determined.
Vapour density	Not determined.
Relative density	0.965g/cm ³ @ 20°C
Solubility(ies)	Insoluble in water.
Partition coefficient	log Pow: -0.24
Auto-ignition temperature	Not determined.
Decomposition Temperature	Not determined.
Viscosity	~1000 cP @ 20°C

9.2. Other information

Other information	None.
-------------------	-------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product. Vapours may form explosive mixtures with air.
------------	---

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
-----------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Not relevant.
------------------------------------	---------------

10.4. Conditions to avoid

Conditions to avoid	Avoid heat, flames and other sources of ignition. Avoid exposure to high temperatures or direct sunlight.
---------------------	---

10.5. Incompatible materials

Materials to avoid	No specific material or group of materials is likely to react with the product to produce a hazardous situation.
--------------------	--

10.6. Hazardous decomposition products

Hazardous decomposition products	Does not decompose when used and stored as recommended.
----------------------------------	---

TRADE SPRAY GLOSS BLACK

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) Butyl Acetate - norm

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 7,400.0

Species Rat

ATE dermal (mg/kg) 22,882.95

Acute toxicity - inhalation

ATE inhalation (gases ppm) 93,612.05

ATE inhalation (vapours mg/l) 228.83

ATE inhalation (dusts/mists mg/l) 31.2

Carcinogenicity

Carcinogenicity Does not contain any substances known to be carcinogenic.

Reproductive toxicity

Reproductive toxicity - fertility Suspected reproductive toxicant based on limited evidence.

Specific target organ toxicity - single exposure

STOT - single exposure Central nervous system depression including narcotic effects such as drowsiness, narcosis, reduced alertness, loss of reflexes, lack of coordination and vertigo.

Target organs Central nervous system

Specific target organ toxicity - repeated exposure

STOT - repeated exposure NOAEL 900 mg/kg, Oral, Rat

Target organs Skin

Aspiration hazard

Aspiration hazard Not applicable.

General information

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Inhalation

Vapour from this product may be hazardous by inhalation. Vapours have a narcotic effect. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Nausea, vomiting.

Ingestion

No harmful effects expected from quantities likely to be ingested by accident.

Skin contact

Contains components which may penetrate the skin. Repeated exposure may cause skin dryness or cracking.

Eye contact

Vapour or spray in the eyes may cause irritation and smarting.

Acute and chronic health hazards

This chemical can be hazardous when inhaled and/or touched. This product may cause skin and eye irritation. Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Route of entry

Inhalation Ingestion. Skin and/or eye contact Skin absorption

TRADE SPRAY GLOSS BLACK

Target organs	Central nervous system Eyes Skin
Medical symptoms	Skin irritation. Irritation of eyes and mucous membranes. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo.
Medical considerations	Skin disorders and allergies. Pre-existing eye problems.

SECTION 12: Ecological Information

Ecotoxicity	Dangerous for the environment if discharged into watercourses.
--------------------	--

12.1. Toxicity

Acute toxicity - fish

LC50, 96 hours: 5540 mg/l, Onchorhynchus mykiss (Rainbow trout)
Butyl Acetate - norm

Acute toxicity - aquatic invertebrates

EC₅₀, 48 hours: 44 mg/l, Daphnia magna

12.2. Persistence and degradability

Persistence and degradability	The product is readily biodegradable. Volatile substances are degraded in the atmosphere within a few days.
--------------------------------------	---

12.3. Bioaccumulative potential

Bioaccumulative potential	The product does not contain any substances expected to be bioaccumulating. BCF: 3,
----------------------------------	---

Partition coefficient	log Pow: -0.24
------------------------------	----------------

12.4. Mobility in soil

Mobility	The product is soluble in water.
-----------------	----------------------------------

Adsorption/desorption coefficient	Not available.
--	----------------

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	This substance is not classified as PBT or vPvB according to current EU criteria.
---	---

12.6. Other adverse effects

Other adverse effects	Not available.
------------------------------	----------------

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information	Waste is classified as hazardous waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Do not puncture or incinerate, even when empty.
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Confirm disposal procedures with environmental engineer and local regulations.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	1950
-------------------------	------

UN No. (IMDG)	1950
----------------------	------

TRADE SPRAY GLOSS BLACK

UN No. (ICAO) 1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID) AEROSOLS

Proper shipping name (IMDG) AEROSOLS

Proper shipping name (ICAO) AEROSOLS

Proper shipping name (ADN) AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID label 2.1

IMDG class 2.1

ICAO class/division 2.1

Transport labels



14.4. Packing group

ADR/RID packing group #

IMDG packing group #

ICAO packing group #

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

EmS F-D, S-U

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78
and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations EH40/2005 Workplace exposure limits

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

TRADE SPRAY GLOSS BLACK

SECTION 16: Other information

Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Revision date	09/10/2013
Revision	13
Supersedes date	13/09/2012 v12
SDS status	Approved.
Hazard statements in full	H222 Extremely flammable aerosol. H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H229 Pressurised container: may burst if heated H312 Harmful in contact with skin. H315 Causes skin irritation. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H360D May damage the unborn child.