

PRODUCT INFORMATION SHEET

BLUECOL 5 YEAR ANTIFREEZE

DESCRIPTION

Bluecol Five Year Antifreeze is a superior quality Ethylene Glycol product incorporating the latest organic acid technology to provide outstanding protection against frost, corrosion and overheating in all modern engines, especially highly loaded aluminium types. Volkswagen approved product for all applications.

ADVANTAGES

- Protection for life coolant minimum five years
- Mixed fleet protection one coolant for cars, vans and trucks (petrol and diesel)
- Protects all types of engines, particularly highly loaded aluminium, where red antifreeze coolant is specified
- Contains a bittering agent to prevent accidental swallowing
- Maintenance free low additive depletion
- Excellent compatibility with seals, hoses and plastic components
- Silicate free
- Helps prevent winter freezing and summer boil over

PERFORMANCE LEVEL

- BS6580 : 2010
- VW/AUDI/SEAT/SKODA (G12 / TL-774D, G12+ / TL-744F)

PROPERTIES

Appearance		Clear Liquid
Colour		Fluorescent Red
Density @ 20℃		1.125
pH (1:2 dilution with water)		8.00
Reserve Alkalinity (ml)		>20
Boiling Point (℃)		>165
Freezing Point (℃)	1:1	-37
	1:2	-17

NOTES

- To obtain optimum protection a 50/50 antifreeze and water mixture is recommended.
- Bluecol Five Year Antifreeze is compatible with good quality traditional (Blue/Green) silicate antifreezes
 however it is not recommended that the two types be mixed as this would completely negate any extended
 life characteristics of the five year product. It is for this reason that extended life antifreezes are coloured
 Red/Orange.
- It is recommended to thoroughly flush through the system with clean water if a conventional coolant (i.e. blue/green/yellow colour) has been used previously.
- If neat fluid is spilled onto paintwork, rinse off immediately.

AVAILABILITY

1 Litre – BCR001 2.5 Litre – BCR025 5 Litre – BCR005 25 Litre – BCR225

5/15/2012 Page 1 of 2



DISCLAIMER

This Product Information Sheet does not constitute to any extent a fitness for purpose warranty or a quality specification. It is intended to be indicative only of the general characteristics of the product(s) and may not be relied upon (in whole or in part) in substitution of nor as a supplement to any of the information and/or instructions and/or warnings set out on the product(s) and/or on any packaging and/or in the relevant Safety Data Sheet (which is available on request).

Neither of the publisher of this Product Information Sheet or the product(s) manufacturer accepts liability for the failure of any person to observe and follow the information and/or instructions and/or warnings on the product(s) and/or on any packaging and/or in the relevant Safety Data Sheet.

Any person selecting and using or causing the product(s) to be used for a specific purpose or any third party recommending the product(s) for a specific purpose without in either case first making all appropriate inquiries as to the suitability of the product(s) for the intended purpose does so at his/her/their own risk and no liability is accepted by the publisher or the product(s) manufacturer for any consequent loss, damage or injury, other than such liability as may not (by operation of law) be excluded.

This Product Information Sheet does not apply to the use of the product(s) in any combination or with other products or materials.

Users of a product or products marked "For Professional Use Only are deemed to declare and acknowledge for themselves professional levels of skill, knowledge, competence and experience in the selection and use of such product(s).

Product Information Sheets are updated from time to time and inquiries should be made on a regular basis to ensure that this is the latest version available.

TETROSYL LIMITED BEVIS GREEN WORKS WALMERSLEY BURY BL9 6RE 0161 764 5981 0161 797 5899 info@tetrosyl.com