



PRODUCT INFORMATION SHEET

BLUECOL ENGINE COOLANT OE 30/34

DESCRIPTION

Bluecol Engine Coolant OE 30/34 is a high quality ethylene glycol based coolant/antifreeze for passenger car, truck, bus & stationary engine application. This has proven to provide protection for at least 650,000km (ca 8000 hours) in truck and bus applications or 250,000km (ca 2000 hours) for passenger cars or 32,000 hours (or 6 years) for stationary engines. It is recommended to change the coolant every five years or at above mileages or operating times, whichever comes first. Bluecol Coolant OE 30/34 meets the original equipment manufacturer (OEM) requirements for:

ASTM D3306, D4656, D4985, BR 637, BS 6580, NFR 15-601, FVV Heft R443, JASO M325, JIS K2234, KSM 2142, MIL-Belgium BT-PS-606 A, MIL-France DCSEA 615/C, MIL-Italy E/L 1415b, MIL-Sweden FSD 8704, NATO S-759, Onorm V5123, SAE J1304, UNE 26-361-88/1, ADE, Aston Martin, Audi TL-774-D/F, Behr, Caterpillar MAK A4.05.09.01, Claas, Cummins IS Series u N14, DAF 74002, MB 325.3, Detroit Diesel Power Cool Plus, Deutz 0199-99-1115/6, Deutz-MWM 0199-99-2091/8, Ford WSS-M97B44-D/E, Chevrolet, Hitachi, Isuzu, Jaguar CMR 8229, Jaguar WSS-M97B44-D, Jenbacher TA 1000-0201, Karosa, Kobelco, Komatsu 07.892, Land Rover WSS-M97B44-D, Leyland Trucks DW03245403, Liebherr MD1-136-130, Mack 014 GS 17009, MAN 324 Typ SNF, MAN B & W AG D36 5600, MAN B & W AS, MAN Semp Pielstick, Mazda MEZ MN 121 D, MG Rover, Mitsubishi MHI, MTU MTL 5048 & 5049, Opel/Vauxhall B 040 1065, Renault 41-01-001/- - S Type D, Saab GM 6277M, Seat TL-774-D/F, Skoda TL-774-D/F, Suzuki Motors, Thermo King, Ulstein Bergen 2.13.01, Vauxhall GME L1301, Volvo 128 6083/002, VW TL-774-D/F, Wartsila, Waukesha, Yanmar.

ADVANTAGES

- Conforms to BS6580 (2010)
- All year round use
- Maintenance free
- Excellent compatibility with seals, hoses and plastic components
- Excellent corrosion protection
- Helps prevent winter freezing down to -36 degrees and summer boil over

PROPERTIES

| | |
|------------------------------|----------------|
| Appearance | Clear Liquid |
| Colour | Red |
| Density @ 20°C | 1.112 |
| pH (1:1 dilution with water) | 8.00 |
| Reserve Alkalinity (ml) | 6.0 |
| Boiling Point (°C) | 160 |
| Freezing Point (°C) | 1:1 V/V -36 |

NOTES

- To obtain optimum protection a 50/50 coolant and water mixture is recommended.
- It is recommended to drain & flush the system with clean water.
- If neat fluid is spilled onto paintwork, rinse off with water.

AVAILABILITY

1L- BEL001 5L- BEL005 20L- BEL200

Tetrosyl



DISCLAIMER

This Product Information Sheet does not constitute to any extent a fitness for purpose warranty or a quality specification. It is intended to be indicative only of the general characteristics of the product(s) and may not be relied upon (in whole or in part) in substitution of nor as a supplement to any of the information and/or instructions and/or warnings set out on the product(s) and/or on any packaging and/or in the relevant Safety Data Sheet (which is available on request).

Neither of the publisher of this Product Information Sheet or the product(s) manufacturer accepts liability for the failure of any person to observe and follow the information and/or instructions and/or warnings on the product(s) and/or on any packaging and/or in the relevant Safety Data Sheet.

Any person selecting and using or causing the product(s) to be used for a specific purpose or any third party recommending the product(s) for a specific purpose without in either case first making all appropriate inquiries as to the suitability of the product(s) for the intended purpose does so at his/her/their own risk and no liability is accepted by the publisher or the product(s) manufacturer for any consequent loss, damage or injury, other than such liability as may not (by operation of law) be excluded.

This Product Information Sheet does not apply to the use of the product(s) in any combination or with other products or materials.

Users of a product or products marked "For Professional Use Only are deemed to declare and acknowledge for themselves professional levels of skill, knowledge, competence and experience in the selection and use of such product(s).

Product Information Sheets are updated from time to time and inquiries should be made on a regular basis to ensure that this is the latest version available.

TETROSYL LIMITED
BEVIS GREEN WORKS
WALMERSLEY
BURY
BL9 6RE
0161 764 5981
0161 797 5899
info@tetrosyl.com