

SAFETY DATA SHEET CARLUBE DOT 3 BRAKE FLUID

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name CARLUBE DOT 3 BRAKE FLUID

Product number BRF050

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Brake fluid.

1.3. Details of the supplier of the safety data sheet

Supplier TETROSYL EUROPE

79 rue du chemin vert

59.273 Fretin

TEL: 03 20 28 06 30 qualite@tetrosyl-france.com

Manufacturer TETROSYL LIMITED

Bury Lancashire England BL9 7NY 0161 764 5981

0161 797 5899 info@tetrosyl.com

1.4. Emergency telephone number

Emergency telephone 0161 764 5981

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (SI 2019 No. 720)

Physical hazards Not Classified

Health hazards Eye Irrit. 2 - H319 Repr. 2 - H361d STOT RE 2 - H373

Environmental hazards Not Classified

2.2. Label elements

Hazard pictograms





Signal word Warning

Hazard statements H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

CARLUBE DOT 3 BRAKE FLUID

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe vapour/ spray.

P264 Wash contaminated skin thoroughly after handling.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/ attention.

P314 Get medical advice/ attention if you feel unwell.

P337+P313 If eye irritation persists: Get medical advice/ attention.

P405 Store locked up.

P501 Dispose of contents/ container in accordance with national regulations.

Contains

2,2'-OXYBISETHANOL, TRIS[2-[2-(2-METHOXYETHOXY)ETHOXY]ETHYL]

ORTHOBORATE

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

2-[2-(2-BUTOXYETHOXY)ETHOXY]ETHANOL

10-<30%

10-<30%

CAS number: 143-22-6 EC number: 205-592-6

Classification

Eye Dam. 1 - H318

2,2' -OXYBISETHANOL

CAS number: 111-46-6 EC number: 203-872-2

Classification

Acute Tox. 4 - H302 STOT RE 2 - H373

TRIS[2-[2-(2-METHOXYETHOXY)ETHOXY]ETHYL]

10-<30%

ORTHOBORATE

CAS number: 30989-05-0 EC number: 250-418-4

Classification

Repr. 2 - H361fd

BUTYL POLYGLYCOL 10-<30%

Classification

Eye Irrit. 2 - H319

CARLUBE DOT 3 BRAKE FLUID

2-(2-METHOXYETHOXY)ETHANOL 2-<3%

CAS number: 111-77-3 EC number: 203-906-6

Classification Repr. 2 - H361d

2-(2-BUTOXYETHOXY)ETHANOL 2-<3%

CAS number: 112-34-5 EC number: 203-961-6

Classification
Eye Irrit. 2 - H319

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Effects may be delayed. Keep affected person under observation. For breathing difficulties,

oxygen may be necessary. If breathing stops, provide artificial respiration. Get medical attention. Remove affected person from source of contamination. Place unconscious person on the side in the recovery position and ensure breathing can take place. Never give anything

by mouth to an unconscious person.

Inhalation Remove affected person from source of contamination. Get medical attention if any discomfort

continues. For breathing difficulties, oxygen may be necessary. If breathing stops, provide artificial respiration. If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. If throat irritation or coughing persists, proceed as follows. Get medical attention. Show this Safety Data Sheet

to the medical personnel.

Ingestion Get medical attention immediately. Never give anything by mouth to an unconscious person.

Try to induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Rinse mouth thoroughly with water. Give plenty of water to drink. Get medical attention if a large quantity has been ingested. Show this Safety Data Sheet to the medical

personnel.

Skin contact Remove contaminated clothing and rinse skin thoroughly with water. Get medical attention if

any discomfort continues.

Eye contact Do not rub eye. Rinse immediately with plenty of water. Remove any contact lenses and open

eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if irritation

persists after washing. Show this Safety Data Sheet to the medical personnel.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure. Effects may be delayed. Keep affected person under observation.

Inhalation Irritation of nose, throat and airway.

Ingestion May cause discomfort if swallowed. May cause unconsciousness, blindness and possibly

death. Central nervous system depression.

Skin contact Prolonged skin contact may cause redness and irritation.

Eye contact Irritation, burning, lachrymation, blurred vision after liquid splash.

CARLUBE DOT 3 BRAKE FLUID

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor
No specific recommendations. If in doubt, get medical attention promptly.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with the following media: Foam, carbon dioxide or dry powder. Use fire-

extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards No unusual fire or explosion hazards noted.

Hazardous combustion

products

Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during

firefighting

No specific firefighting precautions known.

Special protective equipment

for firefighters

Leave danger zone immediately. Use protective equipment appropriate for surrounding

materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. Avoid inhalation

of spray mist and contact with skin and eyes. In case of spills, beware of slippery floors and

surfaces.

6.2. Environmental precautions

Environmental precautionsCollect and dispose of spillage as indicated in Section 13. Avoid release to the environment.

Avoid discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Eliminate all sources of ignition. No smoking, sparks, flames

or other sources of ignition near spillage. Provide adequate ventilation. Provide adequate ventilation. Contain spillage with sand, earth or other suitable non-combustible material. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb spillage with non-

combustible, absorbent material.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet. For waste

disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

CARLUBE DOT 3 BRAKE FLUID

Usage precautions

Read and follow manufacturer's recommendations. Keep away from heat, sparks and open flame. Wear suitable protective equipment for prolonged exposure and/or high concentrations of vapours, spray or mist. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using the product. Avoid inhalation of vapours/spray and contact with skin and eyes. Avoid the formation of mists. Observe any occupational exposure limits for the product or ingredients. Avoid inhalation of vapours and spray/mists. Pregnant or breastfeeding women should not work with this product if there is any risk of exposure. Pregnant or breastfeeding women should not work with this product if there is any risk of exposure.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from heat, sparks and open flame. Keep container tightly closed. Keep containers

upright. Keep only in the original container. Avoid contact with oxidising agents.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

2,2' -OXYBISETHANOL

Long-term exposure limit (8-hour TWA): WEL 23 ppm 101 mg/m³

2-(2-METHOXYETHOXY)ETHANOL

Long-term exposure limit (8-hour TWA): WEL 10 ppm(Sk) 50.1 mg/m3(Sk)

2-(2-BUTOXYETHOXY)ETHANOL

Long-term exposure limit (8-hour TWA): WEL 10 ppm 67.5 mg/m³ Short-term exposure limit (15-minute): WEL 15 ppm 101.2 mg/m³ WEL = Workplace Exposure Limit.

8.2. Exposure controls

Protective equipment





Appropriate engineering

controls

Avoid inhalation of vapours. Observe any occupational exposure limits for the product or

ingredients.

Eye/face protection The following protection should be worn: Chemical splash goggles or face shield.

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn if

a risk assessment indicates skin contact is possible.

Other skin and body

protection

Wear appropriate clothing to prevent reasonably probable skin contact.

Hygiene measures

Use engineering controls to reduce air contamination to permissible exposure level. Provide

eyewash station. Wash contaminated clothing before reuse. Wash at the end of each work

shift and before eating, smoking and using the toilet.

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

CARLUBE DOT 3 BRAKE FLUID

Appearance Liquid.

Colour Light (or pale). Yellow.

Odour Mild.

pH (concentrated solution): 7.0 - 10.5

Melting point <-50°C

Initial boiling point and range >210°C @ 1013 hPa

Flash point 126°C

Evaporation rate Not determined.

Upper/lower flammability or

explosive limits

Not determined.

Vapour density Not determined.

Relative density 1.01 - 1.06g/cm³ @ 20°C

Solubility(ies) Miscible with water. Miscible with the following materials: Ethanol.

Auto-ignition temperature >280°C

Viscosity 5 - 10 cSt @ 20°C

9.2. Other information

Other information None.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability The substance is hygroscopic and will absorb water by contact with the moisture in the air.

10.3. Possibility of hazardous reactions

Possibility of hazardous

Not determined.

reactions

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents. Strong acids. Strong alkalis. Water, steam, water mixtures.

10.6. Hazardous decomposition products

Hazardous decomposition Therma vapours

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or

vapours. Oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects No information available.

Acute toxicity - oral

Summary Based on available data the classification criteria are not met.

CARLUBE DOT 3 BRAKE FLUID

ATE oral (mg/kg) 2,083.33

Acute toxicity - dermal

Summary Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Summary Based on available data the classification criteria are not met.

Skin corrosion/irritation

Summary Based on available data the classification criteria are not met.

Serious eye damage/irritation

Summary Based on available data the classification criteria are not met.

Respiratory sensitisation

Summary Based on available data the classification criteria are not met.

Skin sensitisation

Summary Based on available data the classification criteria are not met.

Germ cell mutagenicity

Summary Based on available data the classification criteria are not met.

Carcinogenicity

Summary Based on available data the classification criteria are not met.

Reproductive toxicity

Summary Based on available data the classification criteria are not met.

Reproductive toxicity -

development

Suspected of damaging the unborn child.

Specific target organ toxicity - single exposure

Summary Based on available data the classification criteria are not met.

Target organs Central nervous system Heart and cardiovascular system Kidneys

Specific target organ toxicity - repeated exposure

Summary Based on available data the classification criteria are not met.

Aspiration hazard

Summary Based on available data the classification criteria are not met.

Inhalation Unlikely to be hazardous by inhalation because of the low vapour pressure of the product at

ambient temperature. Vapours may irritate throat/respiratory system. Symptoms following

overexposure may include the following: Coughing.

Ingestion May cause liver and/or renal damage. Irritating. Symptoms following overexposure may

include the following: Nausea, vomiting. Stomach pain. Harmful: possible risk of irreversible

effects if swallowed.

Skin contact Slightly irritating.

Eye contact Irritating to eyes.

Acute and chronic health

hazards

May cause liver and/or renal damage. Possible risk of adverse reproductive effects. A single exposure may cause the following adverse effects: Central nervous system depression. May cause damage to the kidneys. May cause damage to the kidneys. Contains a substance/a

group of substances which may damage fertility and the unborn child.

CARLUBE DOT 3 BRAKE FLUID

Route of exposure Ingestion.

Target organs Central nervous system Heart & cardiovascular system Kidneys

Medical symptoms Allergic rash. Delayed, often serious, breathing problems. Tachycardia (excessively rapid

heart beat, including rapid and weak pulse). Unconsciousness, possibly death.

SECTION 12: Ecological information

Ecotoxicity The product components are not classified as environmentally hazardous. However, large or

frequent spills may have hazardous effects on the environment.

12.1. Toxicity

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: >100mg/l mg/l, Fish

Acute toxicity - aquatic

invertebrates

Not available.

12.2. Persistence and degradability

Persistence and degradability The product is biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential The product is not bioaccumulating.

12.4. Mobility in soil

Mobility The product is miscible with water. May spread in water systems.

Adsorption/desorption

coefficient

Not available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This substance is not classified as PBT or vPvB according to current UK criteria.

12.6. Other adverse effects

Other adverse effects Not applicable.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste is classified as hazardous waste. Dispose of waste to licensed waste disposal site in

accordance with the requirements of the local Waste Disposal Authority.

Disposal methodsConfirm disposal procedures with environmental engineer and local regulations.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

CARLUBE DOT 3 BRAKE FLUID

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable. **Annex II of MARPOL 73/78**

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009

No. 716).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

General information Only trained personnel should use this material.

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.

Issued by Regulatory Department

Revision date 07/04/2022

Revision 18

Supersedes date 24/01/2022 SDS status Approved.

Hazard statements in full H302 Harmful if swallowed.

H318 Causes serious eye damage. H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

The information provided in this document has been compiled on the basis of our current knowledge and is believed to be in accordance with the requirements of the Dangerous Substances Directive, Dangerous Preparations Directive and Safety Data Sheets Directive. The information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any particular conditions or process. The conditions and extent of storage and use of material are outside of our control and within the control of the possessor or user. Consequently it is the responsibility of the possessor or user to satisfy themselves as to the completeness of such information and the suitability of the material for their own particular circumstances, conditions or use.