



SAFETY DATA SHEET DPF CLEANER

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name DPF CLEANER

Product number DPF300, CNF300, QWC118

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Fuel additive.

1.3. Details of the supplier of the safety data sheet

Supplier TETROSYL LIMITED
Bury
Lancashire
England
BL9 7NY
0161 764 5981
0161 797 5899
info@tetrosyl.com

Manufacturer TETROSYL LIMITED
Bury
Lancashire
England
BL9 7NY
0161 764 5981
0161 797 5899
info@tetrosyl.com

1.4. Emergency telephone number

Emergency telephone +44 (0)161 764 5981

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Asp. Tox. 1 - H304

Environmental hazards Aquatic Chronic 3 - H412

2.2. Label elements

Pictogram



Signal word Danger

DPF CLEANER

Hazard statements	H304 May be fatal if swallowed and enters airways. H412 Harmful to aquatic life with long lasting effects.
Precautionary statements	P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P273 Avoid release to the environment. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P331 Do NOT induce vomiting. P405 Store locked up. P501 Dispose of contents/ container in accordance with national regulations.
Contains	DISTILLATES (PETROLEUM), HYDROTREATED LIGHT; Kerosine - UNSPECIFIED, DISTILLATES (PETROLEUM) HYDROTREATED LIGHT

2.3. Other hazards

Not applicable.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT; KEROSINE - UNSPECIFIED			60-100%
CAS number: —	EC number: 926-141-6	REACH registration number: 01-2119484819-18-0001	
Classification Asp. Tox. 1 - H304			
2-ETHYLHEXYL NITRATE			5-<10%
CAS number: 27247-96-7	EC number: 248-363-6	REACH registration number: 01-2119539586-27-0000	
Classification Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Aquatic Chronic 2 - H411			
DISTILLATES (PETROLEUM) HYDROTREATED LIGHT			2.5-<5.0%
CAS number: 64742-47-8	EC number: 265-149-8	REACH registration number: 01-2119484819-18-0001	
Classification Asp. Tox. 1 - H304			

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

DPF CLEANER

General information	Remove affected person from source of contamination. Effects may be delayed. Keep affected person under observation. Move affected person to fresh air at once. Keep affected person away from heat, sparks and flames. Place unconscious person on the side in the recovery position and ensure breathing can take place. Keep the affected person warm and at rest. Get prompt medical attention.
Inhalation	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Keep affected person under observation. Get medical attention. Show this Safety Data Sheet to the medical personnel.
Ingestion	Rinse mouth thoroughly with water. Give plenty of water to drink. Give milk instead of water if readily available. Keep affected person under observation. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention immediately. Show this Safety Data Sheet to the medical personnel. Never give anything by mouth to an unconscious person. Keep affected person away from heat, sparks and flames.
Skin contact	Remove contaminated clothing and rinse skin thoroughly with water. Get medical attention if any discomfort continues.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Do not rub eye. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure. Effects may be delayed. Keep affected person under observation.
Inhalation	Vapours in high concentrations are anaesthetic. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Central nervous system depression.
Ingestion	May cause discomfort if swallowed. May cause stomach pain or vomiting. May cause nausea, headache, dizziness and intoxication. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation. Congestion of the lungs may occur, producing severe shortness of breath.
Skin contact	Prolonged or repeated contact with skin may cause irritation, redness and dermatitis.
Eye contact	May cause temporary eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations. If in doubt, get medical attention promptly.
-----------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with alcohol-resistant foam, carbon dioxide or dry powder. Use fire-extinguishing media suitable for the surrounding fire.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	May form explosive mixture with air at very high concentration. Containers can burst violently or explode when heated, due to excessive pressure build-up.
Hazardous combustion products	Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

5.3. Advice for firefighters

DPF CLEANER

Protective actions during firefighting No specific firefighting precautions known.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Use suitable respiratory protection if ventilation is inadequate. No smoking, sparks, flames or other sources of ignition near spillage. Avoid contact with skin and eyes. In case of spills, beware of slippery floors and surfaces. For personal protection, see Section 8. Avoid inhalation of vapours and contact with skin and eyes.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground. Avoid the spillage or runoff entering drains, sewers or watercourses. Avoid discharge to the aquatic environment. Collect and dispose of spillage as indicated in Section 13.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up For waste disposal, see Section 13. Stop leak if possible without risk. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Provide adequate ventilation. Contain spillage with sand, earth or other suitable non-combustible material. Avoid the spillage or runoff entering drains, sewers or watercourses. Cover large spillages with alcohol-resistant foam. Absorb spillage with inert, damp, non-combustible material. Flush contaminated area with plenty of water. Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13.

6.4. Reference to other sections

Reference to other sections For waste disposal, see section 13. For personal protection, see Section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. Eliminate all sources of ignition. Keep away from heat, sparks and open flame. Static electricity and formation of sparks must be prevented. Do not eat, drink or smoke when using the product. Avoid inhalation of vapours/spray and contact with skin and eyes. Good personal hygiene procedures should be implemented. Mechanical ventilation or local exhaust ventilation may be required. Provide adequate ventilation.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep container tightly closed. Keep containers upright. Keep only in the original container. Avoid contact with oxidising agents. Do not store near heat sources or expose to high temperatures.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

No exposure limits known for ingredient(s).

DISTILLATES (PETROLEUM) HYDROTREATED LIGHT

Long-term exposure limit (8-hour TWA): WEL 1000 mg/m³

Short-term exposure limit (15-minute): WEL

DPF CLEANER

WEL = Workplace Exposure Limit

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients. Provide adequate ventilation.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended. It is recommended that gloves are made of the following material: Nitrile rubber.

Other skin and body protection

Provide eyewash station. Wear appropriate clothing to prevent repeated or prolonged skin contact.

Hygiene measures

When using do not eat, drink or smoke. Wash hands after contact. Wash at the end of each work shift and before eating, smoking and using the toilet. Wash contaminated clothing before reuse.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. Wear a respirator fitted with the following cartridge: Gas filter, type A2.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Clear liquid.
Colour	Yellow.
Odour	Hydrocarbons.
pH	Not determined.
Melting point	Not determined.
Initial boiling point and range	175°C @
Flash point	>62°C
Evaporation rate	Not determined.
Upper/lower flammability or explosive limits	Not determined.
Vapour pressure	Not determined.
Vapour density	Not determined.
Relative density	0.816g/cm ³ @ 20°C
Solubility(ies)	Insoluble in water.
Partition coefficient	Not determined.
Auto-ignition temperature	Not determined.

DPF CLEANER

Decomposition Temperature Not determined.

Viscosity <50 cP @ 20°C

9.2. Other information

Other information None.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Oxidising materials.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Not relevant.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Does not decompose when used and stored as recommended.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 5,960.9

Acute toxicity - dermal

ATE dermal (mg/kg) 13,113.97

Acute toxicity - inhalation

ATE inhalation (gases ppm) 53,648.07

ATE inhalation (vapours mg/l) 131.14

ATE inhalation (dusts/mists mg/l) 17.88

General information Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Inhalation Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

Ingestion Harmful: may cause lung damage if swallowed. Pneumonia may be the result if vomited material containing solvents reaches the lungs.

Skin contact Prolonged and frequent contact may cause redness and irritation.

Eye contact May cause temporary eye irritation.

DPF CLEANER

Acute and chronic health hazards	Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.
Route of exposure	Ingestion.
Medical considerations	Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

SECTION 12: Ecological Information

Ecotoxicity	The product contains volatile organic compounds (VOCs) which have a photochemical ozone creation potential. The product contains a substance which is harmful to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.
--------------------	--

12.1. Toxicity

Acute aquatic toxicity

Acute toxicity - fish	LC ₅₀ , 96 hours: 1 - 10mg/l (2-ETHYLHEXYL NITRATE) mg/l, Fish
------------------------------	---

Acute toxicity - aquatic plants	IC ₅₀ , 72 hours: 1 - 10mg/l (2-ETHYLHEXYL NITRATE) mg/l, Algae
--	--

12.2. Persistence and degradability

Persistence and degradability	There are no data on the degradability of this product.
--------------------------------------	---

12.3. Bioaccumulative potential

Bioaccumulative potential	No data available on bioaccumulation.
----------------------------------	---------------------------------------

Partition coefficient	Not determined.
------------------------------	-----------------

12.4. Mobility in soil

Adsorption/desorption coefficient	Not available.
--	----------------

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	This substance is not classified as PBT or vPvB according to current EU criteria.
---	---

12.6. Other adverse effects

Other adverse effects	Not available.
------------------------------	----------------

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information	Waste is classified as hazardous waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
----------------------------	---

Disposal methods	Confirm disposal procedures with environmental engineer and local regulations.
-------------------------	--

SECTION 14: Transport information

General	The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).
----------------	--

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

DPF CLEANER

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78
and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations EH40/2005 Workplace exposure limits.

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.

Issued by Health & Safety Department

Revision date 05/08/2016

Revision 6

Supersedes date 10/05/2016

SDS status Approved.

Hazard statements in full

H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.