



## SAFETY DATA SHEET DIESEL TREATMENT

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name	DIESEL TREATMENT
Product number	QPD300, SDT300, QWC112, SPD301
UFI	UFI: H9WM-8TJA-SK4Y-W88A

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Fuel additive.
-----------------	----------------

#### 1.3. Details of the supplier of the safety data sheet

Supplier	TETROSYL EUROPE 79 rue du chemin vert 59.273 Fretin TEL: 03 20 28 06 30 qualite@tetrosyl-france.com
----------	---

Manufacturer	TETROSYL LIMITED Bury Lancashire England BL9 7NY 0161 764 5981 0161 797 5899 info@tetrosyl.com
--------------	---

#### 1.4. Emergency telephone number

Emergency telephone	+44 (0)161 764 5981 (24 hrs)
---------------------	------------------------------

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (SI 2019 No. 720)

Physical hazards	Not Classified
Health hazards	Asp. Tox. 1 - H304
Environmental hazards	Aquatic Chronic 3 - H412

#### 2.2. Label elements

##### Hazard pictograms



Signal word	Danger
-------------	--------

## DIESEL TREATMENT

<b>Hazard statements</b>	H304 May be fatal if swallowed and enters airways. H412 Harmful to aquatic life with long lasting effects.
<b>Precautionary statements</b>	P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P273 Avoid release to the environment. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P331 Do NOT induce vomiting. P405 Store locked up. P501 Dispose of contents/ container in accordance with national regulations.
<b>Supplemental label information</b>	EUH066 Repeated exposure may cause skin dryness or cracking.
<b>UFI</b>	UFI: H9WM-8TJA-SK4Y-W88A
<b>Contains</b>	DISTILLATES (PETROLEUM), HYDROTREATED LIGHT; KEROSENE - UNSPECIFIED

### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

<b>DISTILLATES (PETROLEUM), HYDROTREATED LIGHT; KEROSENE - UNSPECIFIED</b>		<b>60-100%</b>
CAS number: —	EC number: 926-141-6	
Repeated exposure may cause skin dryness or cracking.		
<b>Classification</b> Asp. Tox. 1 - H304		
<b>2-ETHYLHEXYL NITRATE</b>		<b>2-&lt;3%</b>
CAS number: 27247-96-7	EC number: 248-363-6	UK REACH registration number: UK-01-2930426621-5-0000
<b>Classification</b> Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Aquatic Chronic 2 - H411		

The full text for all hazard statements is displayed in Section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>General information</b>	Remove affected person from source of contamination. Keep the affected person warm and at rest. Get prompt medical attention.
<b>Inhalation</b>	Get medical attention if any discomfort continues. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention. Symptoms of lung oedema (shortness of breath) may develop up to 24 hours after exposure. Show this Safety Data Sheet to the medical personnel.

## DIESEL TREATMENT

<b>Ingestion</b>	Rinse mouth thoroughly with water. Give plenty of water to drink. Get medical attention if a large quantity has been ingested. Show this Safety Data Sheet to the medical personnel.
<b>Skin contact</b>	Remove contaminated clothing immediately and wash skin with soap and water. Rinse with water. Get medical attention if irritation persists after washing.
<b>Eye contact</b>	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Do not rub eye. Get medical attention promptly if symptoms occur after washing.

### 4.2. Most important symptoms and effects, both acute and delayed

<b>General information</b>	The severity of the symptoms described will vary dependent on the concentration and the length of exposure. Effects may be delayed. Keep affected person under observation.
<b>Inhalation</b>	No specific symptoms known.
<b>Ingestion</b>	May cause discomfort if swallowed. May cause stomach pain or vomiting.
<b>Skin contact</b>	Skin irritation. Prolonged or repeated contact with skin may cause irritation, redness and dermatitis. Blistering may occur.
<b>Eye contact</b>	Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain. May cause blurred vision and serious eye damage.

### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Notes for the doctor</b>	No specific recommendations. If in doubt, get medical attention promptly.
-----------------------------	---

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

<b>Suitable extinguishing media</b>	Extinguish with the following media: Foam, carbon dioxide or dry powder. Water. Use fire-extinguishing media suitable for the surrounding fire.
-------------------------------------	---

### 5.2. Special hazards arising from the substance or mixture

<b>Specific hazards</b>	No specific precautions due to the small quantities handled. No unusual fire or explosion hazards noted.
<b>Hazardous combustion products</b>	Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

### 5.3. Advice for firefighters

<b>Protective actions during firefighting</b>	No specific firefighting precautions known.
<b>Special protective equipment for firefighters</b>	Leave danger zone immediately.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

<b>Personal precautions</b>	For personal protection, see Section 8. In case of spills, beware of slippery floors and surfaces. Avoid contact with eyes and prolonged skin contact. Provide adequate ventilation. Avoid inhalation of spray mist and contact with skin and eyes.
-----------------------------	---

### 6.2. Environmental precautions

<b>Environmental precautions</b>	Avoid discharge into drains or watercourses or onto the ground. Collect and dispose of spillage as indicated in Section 13.
----------------------------------	---

### 6.3. Methods and material for containment and cleaning up

## DIESEL TREATMENT

**Methods for cleaning up** Stop leak if possible without risk. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely.

### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8. For waste disposal, see section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Usage precautions** Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Avoid eating, drinking and smoking when using the product. Avoid contact with skin and eyes. Do not handle broken packages without protective equipment.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Keep containers upright. Store in tightly-closed, original container. Keep away from heat, sparks and open flame.

### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure controls/Personal protection

### 8.1. Control parameters

#### 2-ETHYLHEXYL NITRATE (CAS: 27247-96-7)

<b>DNEL</b>	Workers - Dermal; Long term systemic effects: 1 mg/kg Workers - Dermal; Long term local effects: 0.0044 mg/cm <sup>2</sup> Workers - Inhalation; Long term systemic effects: 0.35 mg/m <sup>3</sup> General population - Dermal; Long term systemic effects: 0.52 mg/kg General population - Dermal; Long term local effects: 0.0022 mg/cm <sup>2</sup> General population - Inhalation; Long term systemic effects: 0.0087 mg/cm <sup>2</sup> General population - Oral; Long term systemic effects: 0.025 mg/kg
<b>PNEC</b>	Fresh water; 0.0008 mg/l marine water; 0.00008 mg/l Sediment (Freshwater); 0.00074 mg/kg Sediment (Marinewater); 0.00074 mg/kg Soil; 0.000191 mg/kg STP; 10 mg/l

#### 2-ETHYLHEXAN-1-OL (CAS: 104-76-7)

<b>DNEL</b>	Workers - Dermal; Long term systemic effects: 23 mg/kg Workers - Inhalation; Long term systemic effects: 12.8 mg/m <sup>3</sup> Workers - Inhalation; Long term local effects: 53.2 mg/m <sup>3</sup> Workers - Inhalation; Short term local effects: 53.2 mg/m <sup>3</sup> General population - Dermal; Long term systemic effects: 11.4 mg/kg General population - Inhalation; Long term systemic effects: 2.3 mg/m <sup>3</sup> General population - Inhalation; Long term local effects: 26.6 mg/m <sup>3</sup> General population - Inhalation; Short term local effects: 26.6 mg/m <sup>3</sup> General population - Oral; Long term systemic effects: 1.1 mg/kg
-------------	---

## DIESEL TREATMENT

### PNEC

Fresh water; 0.017 mg/l  
 marine water; 0.002 mg/l  
 Sediment (Freshwater); 0.284 mg/kg  
 Sediment (Marinewater); 0.028 mg/kg  
 Soil; 0.047 mg/kg  
 STP; 10 mg/l

### 8.2. Exposure controls

#### Protective equipment



#### Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours and spray/mists. Observe any occupational exposure limits for the product or ingredients.

#### Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

#### Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Nitrile rubber. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended.

#### Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact. Provide eyewash station.

#### Hygiene measures

Provide eyewash station and safety shower. Wash contaminated clothing before reuse. Wash promptly with soap and water if skin becomes contaminated.

#### Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Appearance	Clear liquid. Oily liquid.
Colour	Straw.
Odour	Organic solvents.
Melting point	Not determined.
Initial boiling point and range	175°C @ 1013 hPa
Flash point	74°C
Evaporation rate	Not determined.
Upper/lower flammability or explosive limits	Not determined.
Vapour pressure	Not determined.
Vapour density	Not determined.
Relative density	0.815g/cm <sup>3</sup> @ 20°C
Solubility(ies)	Insoluble in water.
Partition coefficient	Not determined.

## DIESEL TREATMENT

<b>Auto-ignition temperature</b>	Not determined.
<b>Decomposition Temperature</b>	Not determined.
<b>Viscosity</b>	<50 cP @ 20°C

### 9.2. Other information

<b>Other information</b>	None.
--------------------------	-------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

<b>Reactivity</b>	The following materials may react strongly with the product: Alkaline earth metals. Powdered metal.
-------------------	---

### 10.2. Chemical stability

<b>Stability</b>	No particular stability concerns.
------------------	-----------------------------------

### 10.3. Possibility of hazardous reactions

<b>Possibility of hazardous reactions</b>	Not applicable.
---	-----------------

### 10.4. Conditions to avoid

<b>Conditions to avoid</b>	Avoid heat. Avoid contact with the following materials: Strong oxidising agents.
----------------------------	--

### 10.5. Incompatible materials

<b>Materials to avoid</b>	Strong oxidising agents.
---------------------------	--------------------------

### 10.6. Hazardous decomposition products

<b>Hazardous decomposition products</b>	Does not decompose when used and stored as recommended.
---	---

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity - oral

<b>Summary</b>	Based on available data the classification criteria are not met.
----------------	--

<b>Notes (oral LD<sub>50</sub>)</b>	KEROSENE
-------------------------------------	----------

<b>ATE oral (mg/kg)</b>	17,543.86
-------------------------	-----------

#### Acute toxicity - dermal

<b>Summary</b>	Based on available data the classification criteria are not met.
----------------	--

<b>ATE dermal (mg/kg)</b>	38,596.49
---------------------------	-----------

#### Acute toxicity - inhalation

<b>Summary</b>	Based on available data the classification criteria are not met.
----------------	--

<b>ATE inhalation (gases ppm)</b>	157,894.74
-----------------------------------	------------

<b>ATE inhalation (vapours mg/l)</b>	385.96
--------------------------------------	--------

<b>ATE inhalation (dusts/mists mg/l)</b>	52.63
--	-------

#### Skin corrosion/irritation

<b>Summary</b>	Based on available data the classification criteria are not met.
----------------	--

## DIESEL TREATMENT

### Serious eye damage/irritation

**Summary** Based on available data the classification criteria are not met.

### Respiratory sensitisation

**Summary** Based on available data the classification criteria are not met.

### Skin sensitisation

**Summary** Based on available data the classification criteria are not met.

### Germ cell mutagenicity

**Summary** Based on available data the classification criteria are not met.

### Carcinogenicity

**Summary** Based on available data the classification criteria are not met.

### Reproductive toxicity

**Summary** Based on available data the classification criteria are not met.

### Specific target organ toxicity - single exposure

**Summary** Based on available data the classification criteria are not met.

### Specific target organ toxicity - repeated exposure

**Summary** Based on available data the classification criteria are not met.

### Aspiration hazard

**Summary** Based on available data the classification criteria are not met.

**Inhalation** Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

**Ingestion** Aspiration hazard if swallowed.

**Skin contact** Prolonged and frequent contact may cause redness and irritation.

**Eye contact** May cause temporary eye irritation.

**Medical considerations** Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

## SECTION 12: Ecological information

**Ecotoxicity** Harmful to aquatic life with long lasting effects.

### 12.1. Toxicity

#### Acute aquatic toxicity

**Acute toxicity - fish** LC<sub>50</sub>, 96 hours: 2-5 mg/l, Fish

**Acute toxicity - aquatic invertebrates** EC<sub>50</sub>, 48 hours: 1.4 mg/l, Daphnia magna

**Acute toxicity - aquatic plants** IC<sub>50</sub>, 72 hours: 1-3 mg/l, Algae

### 12.2. Persistence and degradability

**Persistence and degradability** The product is expected to be biodegradable.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential** No data available on bioaccumulation.

**Partition coefficient** Not determined.

## DIESEL TREATMENT

### 12.4. Mobility in soil

<b>Mobility</b>	The product is insoluble in water and will spread on the water surface.
<b>Adsorption/desorption coefficient</b>	Not available.

### 12.5. Results of PBT and vPvB assessment

<b>Results of PBT and vPvB assessment</b>	This substance is not classified as PBT or vPvB according to current UK criteria.
---	---

### 12.6. Other adverse effects

<b>Other adverse effects</b>	Not applicable.
------------------------------	-----------------

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

<b>General information</b>	Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
<b>Disposal methods</b>	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Confirm disposal procedures with environmental engineer and local regulations.

## SECTION 14: Transport information

<b>General</b>	The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).
----------------	--

### 14.1. UN number

Not applicable.

### 14.2. UN proper shipping name

Not applicable.

### 14.3. Transport hazard class(es)

No transport warning sign required.

### 14.4. Packing group

Not applicable.

### 14.5. Environmental hazards

<b>Environmentally hazardous substance/marine pollutant</b>	No.
---	-----

### 14.6. Special precautions for user

Not applicable.

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

<b>Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code</b>	Not applicable.
---	-----------------

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.2. Chemical safety assessment



## DIESEL TREATMENT

No chemical safety assessment has been carried out.

### SECTION 16: Other information

**Classification procedures according to SI 2019 No. 720** Not classified for physical hazards.: On basis of test data.

**Revision comments** NOTE: Lines within the margin indicate significant changes from the previous revision.

**Issued by** Regulatory Department

**Revision date** 31/08/2022

**Revision** 24

**Supersedes date** 25/01/2022

**SDS status** Approved.

**Hazard statements in full**  
H302 Harmful if swallowed.  
H304 May be fatal if swallowed and enters airways.  
H312 Harmful in contact with skin.  
H332 Harmful if inhaled.  
H411 Toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.