

PRODUCT INFORMATION SHEET

TETROSYL'S PROTEX FLOOR PAINT

DESCRIPTION

Tetrosyl Protex Floor Paint protects and coats most solid interior surfaces including concrete, brick, stone, wood, lino, and floor tiles. Protex provides a tough finish, which resists foot and vehicle wear, oil, grease and detergents. It is quick drying and gives a decorative gloss finish that is easy to maintain. To provide slip resistant properties add 10% (approximately 500g) of Tetrosyl Safe Grip Additive. Safe Grip measurements can be altered to suit individual requirements.

Preparation and Priming:

- Ensure that the surface to be painted is dry, clean and free from wax, dust and loose materials. Oil and grease should be removed from concrete floors by using oil and grease removing product such as Tetrosyl White Spirit - avoid excess moisture. Concrete surfaces must be dry and at least four weeks old before applying paint.
- To ensure the surface is free of any contamination's and any previous coatings, clean concrete and stone surfaces with Tetrosyl Brick and Concrete Cleaner and then thoroughly wash off and allow to dry.
- It is recommended to test the product on a trial area first to ensure adhesion and compatibility with previous coatings. Seal very porous surfaces with Tetrosyl Floor Sealer or with a mixture of four parts Tetrosyl Protex Floor Paint to one part Tetrosyl White Spirit. Leave until completely dry.

Application & Drying Times:

Carefully stir paint thoroughly before use (Tetrosyl Safe Grip Additive can be added at this stage). If Safe Grip Additive is used stir frequently to prevent settling. Apply with a brush or roller (pile type recommended). The first coat will take approximately 3 to 4 hours to dry at 20°C (68° F). A second coat can be applied if required after 12 hours under normal drying conditions. Recoating should take place within 48 hours. Ensure that the paint is completely dry before putting the area to use.

Coverage:

Up to 15 square metres per litre depending on surface texture, porosity and method of application. More paint will be needed on porous and/or uneven surfaces.

Storage:


Store upright in cool dry conditions away from direct sunlight. This product is to be stored in a suitable flammable protection store.

Caution:

More than one coat may result in a slippery surface. It is recommended to use 10% (approximately 500g) i.e. 1 bag of Tetrosyl Safe Grip Slip Resistant Additive for areas where safety is important. Protex Floor Paint is not recommended for use on asphalt, P.V.C, thermoplastic tiles or non-porous surfaces, e.g. glazed tiles, power floated concrete and granolithic floors. If it is to be used on a power floated concrete floor, it will require acid etching or vacuum grit blasting to provide a key. Do not use externally, e.g. carports and drives.

AVAILABILITY

5 Lit Metal Tins in Grey & Red colour.

**DISCLAIMER**

This Product Information Sheet does not constitute to any extent a fitness for purpose warranty or a quality specification. It is intended to be indicative only of the general characteristics of the product(s) and may not be relied upon (in whole or in part) in substitution of nor as a supplement to any of the information and/or instructions and/or warnings set out on the product(s) and/or on any packaging and/or in the relevant Safety Data Sheet (which is available on request).

Neither of the publisher of this Product Information Sheet or the product(s) manufacturer accepts liability for the failure of any person to observe and follow the information and/or instructions and/or warnings on the product(s) and/or on any packaging and/or in the relevant Safety Data Sheet.

Any person selecting and using or causing the product(s) to be used for a specific purpose or any third party recommending the product(s) for a specific purpose without in either case first making all appropriate inquiries as to the suitability of the product(s) for the intended purpose does so at his/her/their own risk and no liability is accepted by the publisher or the product(s) manufacturer for any consequent loss, damage or injury, other than such liability as may not (by operation of law) be excluded.

This Product Information Sheet does not apply to the use of the product(s) in any combination or with other products or materials.

Users of a product or products marked "For Professional Use Only are deemed to declare and acknowledge for themselves professional levels of skill, knowledge, competence and experience in the selection and use of such product(s).

Product Information Sheets are updated from time to time and inquiries should be made on a regular basis to ensure that this is the latest version available.

TETROSYL LIMITED
BEVIS GREEN WORKS
WALMERSLEY
BURY
BL9 6RE
0161 764 5981
0161 797 5899
info@tetrosyl.com