



## **PRODUCT INFORMATION SHEET**

Colour Cure 2K Fibrofil

### **Description**

FOR PROFESSIONAL USE ONLY

2 pack polyester glass reinforced repair putty for automotive repairs.

### **Directions For Use**

1. Prepare surface to be filled with a suitable grade of abrasive paper. Remove all loose rust and paint
2. Degrease the surface and ensure all dirt and grease has been removed. Ensure the substrate is fully dried before continuing to step 3.
3. For large holes use Aluminium mesh to bridge the hole and help support the putty.
4. Mix filler putty with hardener paste, 98% putty 2% hardener paste. Avoid air entrainment during mixing.
5. Apply filler to repair and shape to desired finish. Product will set within 5 – 10 minutes at 20°C. Cold conditions will extend setting times, warm temperatures will reduce setting times.
6. Allow 20 minutes to fully set. Sand using P80 grit abrasive paper or finer to achieve the desired shape.
7. This product may be over filled or over painted with most primers, base coats and lacquers.

**IMPORTANT:** Suitable for low bake oven system 80 – 90°C. Never use too much hardener. Never return paste to tin. Keep paste cool in the summer and warm in the winter.

### **AVAILABILITY**

Various sizes

**Tetrostyl**



**DISCLAIMER**

This Product Information Sheet does not constitute to any extent a fitness for purpose warranty or a quality specification. It is intended to be indicative only of the general characteristics of the product(s) and may not be relied upon (in whole or in part) in substitution of nor as a supplement to any of the information and/or instructions and/or warnings set out on the product(s) and/or on any packaging and/or in the relevant Safety Data Sheet (which is available on request).

Neither of the publisher of this Product Information Sheet or the product(s) manufacturer accepts liability for the failure of any person to observe and follow the information and/or instructions and/or warnings on the product(s) and/or on any packaging and/or in the relevant Safety Data Sheet.

Any person selecting and using or causing the product(s) to be used for a specific purpose or any third party recommending the product(s) for a specific purpose without in either case first making all appropriate inquiries as to the suitability of the product(s) for the intended purpose does so at his/her/their own risk and no liability is accepted by the publisher or the product(s) manufacturer for any consequent loss, damage or injury, other than such liability as may not (by operation of law) be excluded.

This Product Information Sheet does not apply to the use of the product(s) in any combination or with other products or materials.

Users of a product or products marked "For Professional Use Only" are deemed to declare and acknowledge for themselves professional levels of skill, knowledge, competence and experience in the selection and use of such product(s).

Product Information Sheets are updated from time to time and inquiries should be made on a regular basis to ensure that this is the latest version available.

TETROSYL LIMITED  
BEVIS GREEN WORKS  
WALMERSLEY  
BURY  
BL9 6RE  
0161 764 5981  
0161 797 5899  
info@tetrostyl.com