

PRODUCT INFORMATION SHEET

TETRION FLEXIBLE WOODFILLER

DESCRIPTION

Tetrium Flexible Wood Filler is an easy-to-use, ready-mixed filler suitable for interior and exterior use. The filler bonds strongly to wood and leaves a water-resistant, super-smooth finish, which can be stained, varnished or painted. Tetrium Flexible Wood Filler is resistant to shrinking or cracking and is suitable for wood-filling repairs to doors, skirting boards, floor boards, window frames, nail holes, etc.

ADVANTAGES

- Super smooth and flexible
- Shrinking and cracking resistant
- Interior/Exterior Use
- Easy sanding
- Can be nailed or screwed
- Rapid drying and low odor

DIRECTIONS FOR USE

- Ensure surfaces are dry clean and free from dust and loose materials. Remove all decayed wood down to dry, sound materials. Allow damp wood to dry completely.
- Stir filler thoroughly to form smooth paste.
- Apply with filling knife, pressing filler firmly into repair. Smooth off.
- Build up deep repairs in layers no more than 5mm. Allow each layer to dry thoroughly before applying next layer. Filler starts to set in approximately 2-3 hours, depending on the depth of the filler and temperature/humidity. Allow thicker layers (above 5mm) to set overnight.
- Once dry, sand smooth and paint, stain or varnish.
- After use, to keep remaining filler in perfect condition, replace plastic disc, cover with damp rag and reseal lid. Wash tools with warm water. Store away from frost.


NOTE: Avoid using in wet or damp conditions. If rain or moisture is expected, cover repair with waterproof material until filler has fully set. Protect from temperatures below 5 °C until set. Filler may stain/varnish differently to surrounding timber. Test on a small area to assess whether appearance is acceptable.

AVAILABILITY

330g – WFN330

400g – WFN401

600g – WFN600

**DISCLAIMER**

This Product Information Sheet does not constitute to any extent a fitness for purpose warranty or a quality specification. It is intended to be indicative only of the general characteristics of the product(s) and may not be relied upon (in whole or in part) in substitution of nor as a supplement to any of the information and/or instructions and/or warnings set out on the product(s) and/or on any packaging and/or in the relevant Safety Data Sheet (which is available on request).

Neither of the publisher of this Product Information Sheet or the product(s) manufacturer accepts liability for the failure of any person to observe and follow the information and/or instructions and/or warnings on the product(s) and/or on any packaging and/or in the relevant Safety Data Sheet.

Any person selecting and using or causing the product(s) to be used for a specific purpose or any third party recommending the product(s) for a specific purpose without in either case first making all appropriate inquiries as to the suitability of the product(s) for the intended purpose does so at his/her/their own risk and no liability is accepted by the publisher or the product(s) manufacturer for any consequent loss, damage or injury, other than such liability as may not (by operation of law) be excluded.

This Product Information Sheet does not apply to the use of the product(s) in any combination or with other products or materials.

Users of a product or products marked "For Professional Use Only are deemed to declare and acknowledge for themselves professional levels of skill, knowledge, competence and experience in the selection and use of such product(s).

Product Information Sheets are updated from time to time and inquiries should be made on a regular basis to ensure that this is the latest version available.

TETROSYL LIMITED
BEVIS GREEN WORKS
WALMERSLEY
BURY
BL9 6RE
0161 764 5981
0161 797 5899
info@tetrosyl.com