

# SAFETY DATA SHEET DRIVEMASTER 5W40 FULLY SYNTHETIC OIL

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name DRIVEMASTER 5W40 FULLY SYNTHETIC OIL

Product number DRF001, DRF005, DRF025, DRF199

1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Engine oil.

1.3. Details of the supplier of the safety data sheet

**Supplier** Andrew Page

Apson House
Colton Mill

Bullerthorpe Lane

Leeds LS15 9JN

Tel: +44 (0) 113 397 0200

Manufacturer TETROSYL LIMITED

Bury Lancashire England BL9 7NY 0161 764 5981 0161 797 5899 info@tetrosyl.com

1.4. Emergency telephone number

**Emergency telephone** +44 (0)161 764 5981

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Not Classified

**Environmental hazards** Aquatic Chronic 3 - H412

2.2. Label elements

**Hazard statements** H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements** P273 Avoid release to the environment.

P501 Dispose of contents/ container in accordance with national regulations. P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

2.3. Other hazards

## DRIVEMASTER 5W40 FULLY SYNTHETIC OIL

# SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

LUBRICATING OILS, (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED <3% DMSO 30-<60%

EXTRACT (IP346)

 REACH registration number: 01-

2119474889-13

Classification

Asp. Tox. 1 - H304

MINERAL OIL - H304 (<3% DMSO EXTRACT, IP 346)

5-<10%

CAS number: 64742-55-8 EC number: 265-158-7 REACH registration number: 01-

2119487077-29-0000

Classification

Asp. Tox. 1 - H304

REACTION PRODUCTS OF BENZENEAMINE, N-PHENYL-

1-<2.5%

WITH NONENE (BRANCHED)

CAS number: — EC number: 253-249-4

REACH registration number: 01-

2119488911-28-0000

Classification

Aquatic Chronic 4 - H413

DODECYLPHENOL, MIXED ISOMERS (BRANCHED)

0.1-<0.3%

CAS number: — EC number: 310-154-3

REACH registration number: 01-

2119513207-49-0000

M factor (Acute) = 10 M factor (Chronic) = 10

Classification

Skin Irrit. 2 - H315

Eye Irrit. 2 - H319

Repr. 2 - H361f

Aquatic Acute 1 - H400

Aquatic Chronic 1 - H410

## DRIVEMASTER 5W40 FULLY SYNTHETIC OIL

DIPHENYLAMINE 0.1-<0.3%

#### Classification

Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 STOT RE 2 - H373 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

The full text for all hazard statements is displayed in Section 16.

#### SECTION 4: First aid measures

## 4.1. Description of first aid measures

General information Get medical attention if any discomfort continues. Remove affected person from source of

contamination. Move affected person to fresh air and keep warm and at rest in a position

comfortable for breathing.

Inhalation If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and

keep warm and at rest in a position comfortable for breathing.

**Ingestion** Contact physician if larger quantity has been consumed. Rinse mouth thoroughly with water.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Continue to rinse for at least 15 minutes. Do not rub eye.

### 4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure. Effects may be delayed. Keep affected person under observation.

Inhalation May cause an asthma-like shortness of breath. Vapours may cause headache, fatigue,

dizziness and nausea.

Ingestion May cause discomfort if swallowed. May cause stomach pain or vomiting. May cause nausea,

headache, dizziness and intoxication.

**Skin contact** Prolonged or repeated contact with skin may cause irritation, redness and dermatitis.

**Eye contact** May cause temporary eye irritation.

## 4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. If in doubt, get medical attention promptly.

## SECTION 5: Firefighting measures

## 5.1. Extinguishing media

Suitable extinguishing media Extinguish with the following media: Foam, carbon dioxide or dry powder. Use fire-

extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

#### 5.2. Special hazards arising from the substance or mixture

## DRIVEMASTER 5W40 FULLY SYNTHETIC OIL

Specific hazards Fire creates: Carbon monoxide (CO). Carbon dioxide (CO2). No unusual fire or explosion

hazards noted.

Hazardous combustion

products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or

vapours. Oxides of carbon.

5.3. Advice for firefighters

Special protective equipment

for firefighters

Leave danger zone immediately.

#### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Follow precautions for safe handling described in

Follow precautions for safe handling described in this safety data sheet. Avoid inhalation of vapours. Avoid contact with eyes and prolonged skin contact. Provide adequate ventilation. In case of spills, beware of slippery floors and surfaces.

#### 6.2. Environmental precautions

**Environmental precautions** 

Avoid or minimise the creation of any environmental contamination. Do not discharge into drains or watercourses or onto the ground. Collect and dispose of spillage as indicated in Section 13.

## 6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Stop leak if possible without risk. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Provide adequate ventilation. Contain spillage with sand, earth or other suitable non-combustible material. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely.

#### 6.4. Reference to other sections

Reference to other sections

Wear protective clothing as described in Section 8 of this safety data sheet. Collect and dispose of spillage as indicated in Section 13. The product contains a substance which is hazardous to aquatic organisms and which may cause long term adverse effects in the aquatic environment. See Section 12 for additional information on ecological hazards.

## SECTION 7: Handling and storage

## 7.1. Precautions for safe handling

Usage precautions

Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using the product. Avoid the formation of mists. Provide adequate ventilation. Always remove oil with soap and water or skin cleaning agent, never use organic solvents. Do not use oil-contaminated clothing or shoes, and do not put rags moistened with oil into pockets.

## 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Keep containers upright. Store in tightly-closed, original container.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure Controls/personal protection

#### 8.1. Control parameters

Occupational exposure limits

## DRIVEMASTER 5W40 FULLY SYNTHETIC OIL

No exposure limits known for ingredient(s).

#### **DIPHENYLAMINE**

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ Short-term exposure limit (15-minute): WEL 20 mg/m³ WEL = Workplace Exposure Limit

#### 8.2. Exposure controls

## Protective equipment







Appropriate engineering

controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Nitrile rubber. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended.

Other skin and body

Hygiene measures

protection

Wear appropriate clothing to prevent repeated or prolonged skin contact.

Wash contaminated clothing before reuse. Wash promptly with soap and water if skin

becomes contaminated.

**Respiratory protection** No specific recommendations.

## SECTION 9: Physical and Chemical Properties

## 9.1. Information on basic physical and chemical properties

Appearance Clear liquid.

Colour Brown.

Odour Mineral. Oil-like.

Odour threshold Not determined.

pH Not determined.

Melting point Not determined.

Initial boiling point and range >250°C @

Flash point 220°C

Evaporation rate Not determined.

Evaporation factor Not determined.

Upper/lower flammability or explosive limits

JI SCI

Scientifically unjustified.

Vapour pressure Not determined.

Vapour density Not determined.

# **DRIVEMASTER 5W40 FULLY SYNTHETIC OIL**

Relative density 0.855g/cm³ @ 20°C

Solubility(ies) Insoluble in water.

Partition coefficient Not determined.

Auto-ignition temperature Not determined.

**Decomposition Temperature** Not determined.

**Viscosity** 85.0 cSt @ 40 @ °C

Oxidising properties Not determined.

9.2. Other information

Other information None.

## SECTION 10: Stability and reactivity

## 10.1. Reactivity

**Reactivity** There are no known reactivity hazards associated with this product.

10.2. Chemical stability

**Stability** No particular stability concerns.

## 10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Not applicable.

10.4. Conditions to avoid

Conditions to avoid There are no known conditions that are likely to result in a hazardous situation.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents.

## 10.6. Hazardous decomposition products

Hazardous decomposition

products

Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapours.

## SECTION 11: Toxicological information

## 11.1. Information on toxicological effects

**Toxicological effects** No information available.

Acute toxicity - oral

**ATE oral (mg/kg)** 87,719.3

Acute toxicity - dermal

**ATE dermal (mg/kg)** 263,157.89

Acute toxicity - inhalation

ATE inhalation (gases ppm) 614,035.09

ATE inhalation (vapours mg/l) 2,631.58

ATE inhalation (dusts/mists

438.6

mg/l)

## SECTION 12: Ecological Information

## DRIVEMASTER 5W40 FULLY SYNTHETIC OIL

**Ecotoxicity** Harmful to aquatic life with long lasting effects.

12.1. Toxicity

Acute toxicity - fish Not available.

Acute toxicity - aquatic Not available.

invertebrates

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined.

12.4. Mobility in soil

**Mobility** The product is insoluble in water.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB This

assessment

This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste is classified as hazardous waste. Dispose of waste to licensed waste disposal site in

accordance with the requirements of the local Waste Disposal Authority.

**Disposal methods**Confirm disposal procedures with environmental engineer and local regulations.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No

14.6. Special precautions for user

# **DRIVEMASTER 5W40 FULLY SYNTHETIC OIL**

Not applicable.

#### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

**Transport in bulk according to** Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

## SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations EH40/2005 Workplace exposure limits

**EU legislation** Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18

December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

#### SECTION 16: Other information

**Revision comments** NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision date 04/02/2014

Revision 25

Supersedes date 29/01/2014 v24

SDS status Approved.

Hazard statements in full H301 Toxic if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin. H315 Causes skin irritation.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H361f Suspected of damaging fertility.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.