



PRODUCT INFORMATION SHEET

CARLUBE 2 STROKE MOTOR OIL

DESCRIPTION

Carlube 2-Stroke Motor Oil contains top quality mineral oil and carefully selected additives which ensure the thermal stability, anti-wear properties, engine cleanliness and protection against corrosion of bearings and cylinders of a modern 2-Stroke engine. The product is suitable for both "in-tank" petrol mix systems and metered lubrication systems.

ADVANTAGES

- Excellent dispersion in fuel
- Clean burning low ash additives
- Low deposits on plugs, exhaust ports, piston rings and crowns
- Contains rust and corrosion inhibitors

APPLICATION

Carlube 2-Stroke Motor Oil is suitable for use in all modern 2-Stroke engines of motorcycles, moped and scooters where the performance level shown below is specified. (Not recommended for high-powered motorcycles).

NOTE: When using 2-Stroke oils always refer to manufacturers handbook for correct quality level and fuel to oil mix ratio.

PERFORMANCE LEVEL

- API TC
- JASO FB

PROPERTIES

Appearance		Clear & Bright
Color		Red
Density @ 15°C		0.885
Kinematic Viscosity (mm ² /s)	@ 40°C	61.0
	@ 100°C	8.00
Viscosity Index (VI)		97
Flash Point (°C)		190

AVAILABILITY

500ml – XST501

1 Litre – XST011

4.55 Litre – XST455

ENVIRONMENTAL PROTECTION/SAFETY PRECAUTIONS

Do not pour used or surplus oil down sewers or drains. Dispose of used or surplus oil at your nearest oil-recycling bank. Dispose of empty packs in a responsible manner. Store container in an upright position and secure when transported. Wear goggles if splashing risk. Avoid exposure to oil mist. When using oil do not eat, drink and smoke. Wash hands after use.

**DISCLAIMER**

This Product Information Sheet does not constitute to any extent a fitness for purpose warranty or a quality specification. It is intended to be indicative only of the general characteristics of the product(s) and may not be relied upon (in whole or in part) in substitution of nor as a supplement to any of the information and/or instructions and/or warnings set out on the product(s) and/or on any packaging and/or in the relevant Safety Data Sheet (which is available on request).

Neither of the publisher of this Product Information Sheet or the product(s) manufacturer accepts liability for the failure of any person to observe and follow the information and/or instructions and/or warnings on the product(s) and/or on any packaging and/or in the relevant Safety Data Sheet.

Any person selecting and using or causing the product(s) to be used for a specific purpose or any third party recommending the product(s) for a specific purpose without in either case first making all appropriate inquiries as to the suitability of the product(s) for the intended purpose does so at his/her/their own risk and no liability is accepted by the publisher or the product(s) manufacturer for any consequent loss, damage or injury, other than such liability as may not (by operation of law) be excluded.

This Product Information Sheet does not apply to the use of the product(s) in any combination or with other products or materials.

Users of a product or products marked "For Professional Use Only are deemed to declare and acknowledge for themselves professional levels of skill, knowledge, competence and experience in the selection and use of such product(s).

Product Information Sheets are updated from time to time and inquiries should be made on a regular basis to ensure that this is the latest version available.

TETROSYL LIMITED
BEVIS GREEN WORKS
WALMERSLEY
BURY
BL9 6RE
0161 764 5981
0161 797 5899
info@tetrosyl.com