



PRODUCT INFORMATION SHEET

CARLUBE ATF-U AUTOMATIC TRANSMISSION FLUID

DESCRIPTION

Carlube ATF-U Transmission Fluid is a high quality universal automatic transmission fluid that has been carefully blended from synthetic basestocks & specially balanced additives, to give a product which satisfies the stringent low temperature & frictional requirements of a wide range of specifications.

ADVANTAGES

- Universal automatic transmission fluid
- Offers smooth and comfortable gear shifting
- Resists thermal & oxidative degradation better than conventional transmission fluids
- Anti-corrosion and rust protection
- Excellent low temperature fluidity
- Can be used as ISO VG32 Hydraulic Oil
- Can be used as Power Steering Fluid

APPLICATION

Whilst primarily recommended for passenger cars, coaches, off-highway construction equipment requiring a Mercon V type fluid, the product is also highly recommended against the shown specifications.

PERFORMANCE LEVEL

TRANSMISSIONS

- | | | |
|---------------------------------|--------------------------------------|------------------------|
| • Ford Mercon V / SP / LV | • GM Dexron VI | • VW G 052 162 |
| • Ford M2C-202-B | • Toyota T-II/IV/WS | • Allison TES-295 |
| • Honda Z-1 (Except CVT) | • Mitsubishi/Hyundai SP II/III | • Nissan Matic D/J |
| • JWS 3309 | • BMW LA2634 | • BMW 8072B |
| • BMW 7045E | • MB 236.6/236.7/236.9/236.10/236.11 | • Subaru ATF |
| • Man 339 V-1 / V-2 / Z-1 / Z-2 | • Texaco N402 | • VW/Audi G-055-025-AZ |
| • VW/Audi G-052-162 | • Volvo 1161540/97341 | • LT 71141 |
| • Voith 55.6335.XX (G607) | • Chrysler ATF/ATF 3+/ATF 4+ | |

POWER STEERING

Can be used where any of the above specifications are listed.

PROPERTIES

| Appearance | | Low Viscosity Oil |
|---|---------|-------------------|
| Colour | | Red |
| Density @ 15°C | | 0.854 |
| Kinematic Viscosity (mm ² /s) | @ 40°C | 40.2 |
| | @ 100°C | 7.20 |
| Viscosity Index (VI) | | 198 |
| Pour Point (°C) | | -52 |
| Flash Point (°C) | | 212 |

AVAILABILITY

500ml – XTU500

1 Litre – XTU001

4.55 Litre – XTU455

25 Litre – YFU025

Tetrostyl



DISCLAIMER

This Product Information Sheet does not constitute to any extent a fitness for purpose warranty or a quality specification. It is intended to be indicative only of the general characteristics of the product(s) and may not be relied upon (in whole or in part) in substitution of nor as a supplement to any of the information and/or instructions and/or warnings set out on the product(s) and/or on any packaging and/or in the relevant Safety Data Sheet (which is available on request).

Neither of the publisher of this Product Information Sheet or the product(s) manufacturer accepts liability for the failure of any person to observe and follow the information and/or instructions and/or warnings on the product(s) and/or on any packaging and/or in the relevant Safety Data Sheet.

Any person selecting and using or causing the product(s) to be used for a specific purpose or any third party recommending the product(s) for a specific purpose without in either case first making all appropriate inquiries as to the suitability of the product(s) for the intended purpose does so at his/her/their own risk and no liability is accepted by the publisher or the product(s) manufacturer for any consequent loss, damage or injury, other than such liability as may not (by operation of law) be excluded.

This Product Information Sheet does not apply to the use of the product(s) in any combination or with other products or materials.

Users of a product or products marked "For Professional Use Only" are deemed to declare and acknowledge for themselves professional levels of skill, knowledge, competence and experience in the selection and use of such product(s).

Product Information Sheets are updated from time to time and inquiries should be made on a regular basis to ensure that this is the latest version available.

TETROSYL LIMITED
BEVIS GREEN WORKS
WALMERSLEY
BURY
BL9 6RE
0161 764 5981
0161 797 5899
info@tetrostyl.com